

Surface: smooth, no scratch, dent, spot
 Thickness of Chromium Plating: 0.01 mm - 0.015 mm
 Protection: anti-corrosion oil

POLOTOVAR / DESCRIPTION:	NORMA / DODAVATEL:	WEIGHT:
--------------------------	--------------------	---------

TOLEROVANO ISO 8015 NETOLEROVANE ROZMERY ISO 2768-mK TOLERANCES ISO 8015 NOT SPECIFIED APPLY ISO 2768-mK	MATERIAL: GCr15 (AISI SAE52100)
---	---------------------------------

KRESLIL / DRAWN: Robert Turinský	DATE: 06.05.2019	MERITKO / SCALE: 5 : 1	FORMAT: A4	SHEET: 1 / 2
----------------------------------	------------------	------------------------	------------	--------------


PRUSA RESEARCH by JOSEF PRUSA	Prusa Research s.r.o. Partyzanska 188/7a 170 00 Praha 7 Czech Republic info@prusa3d.com	NAZEV / TITLE: Hlazená tyč 8x330 - kalená (y-axis)-A1
		CISLO / NUMBER: ID44-A1 REV: 1C



A1	12.5.2021	NEW PART	TURINSKÝ
REV	DAT.	POPIS / DESCRIPTION	AUTOR

REVIZNÍ LIST / CHANGELOG

KRESLIL / DRAWN: Robert Turinský	DATE: 13.05.2021	FORMAT: A4	SHEET: 2 / 2
----------------------------------	------------------	------------	--------------

 <p>Prusa Research a.s. Partyzanska 188/7a 170 00 Praha 7 Czech Republic info@prusa3d.com</p>	NAZEV / TITLE: Hlazená tyč 8x330 - kalená (y-axis)-A1	
	CISLO / NUMBER: ID44-A1	REV A1