


Surface: smooth, no scratch, dent, spot
 Thickness of Chromium Plating: 0.01 mm - 0.015 mm
 Protection: anti-corrosion oil

POLOTOVAR / DESCRIPTION:		NORMA / DODAVATEL:		WEIGHT:	
TOLEROVANO ISO 8015 NETOLEROVANE ROZMERY ISO 2768-mK TOLERANCES ISO 8015 NOT SPECIFIED APPLY ISO 2768-mK		MATERIAL: GCr15 (AISI SAE52100)			
KRESLIL / DRAWN: Robert Turinský		DATE: 12.05.2021		MERITKO / SCALE: 5 : 1	FORMAT: A4
MODEL: Hlazená tyč 8x370 - kalená (x-axis).ipt				SHEET: 1 / 2	
PRUSA RESEARCH by JOSEF PRUSA Prusa Research s.r.o. Partyzanska 188/7a 170 00 Praha 7 Czech Republic info@prusa3d.com		NAZEV / TITLE: Hlazená tyč 8x370 - kalená (x-axis)-A2			
		CISLO / NUMBER: ID46-A2		REV: A2	

A2	19.05.2021	TOLERANCE FROM h6 TO h7	TURINSKÝ
A1	12.5.2021	NEW PART	TURINSKÝ
REV	DAT.	POPIS / DESCRIPTION	AUTOR

REVIZNÍ LIST / CHANGELOG

KRESLIL / DRAWN: Robert Turinský	DATE: 12.05.2021	FORMAT: A4	SHEET: 2 / 2
----------------------------------	------------------	------------	--------------

 <p>Prusa Research a.s. Partyzanska 188/7a 170 00 Praha 7 Czech Republic info@prusa3d.com</p>	NAZEV / TITLE: Hlazená tyč 8x370 - kalená (x-axis)-A2	
	CISLO / NUMBER: ID46-A2	REV A2